

OS3D - GoogleCommunication

v 0.1

Generated by Doxygen 1.7.2

Sun Oct 10 2010 02:54:26

Contents

1	Namespace Index	1
1.1	Package List	1
2	Class Index	3
2.1	Class List	3
3	Namespace Documentation	5
3.1	Package GoogleCommunication	5
4	Class Documentation	7
4.1	GoogleCommunication.GoogleEmailer Class Reference	7
4.1.1	Detailed Description	8
4.1.2	Constructor & Destructor Documentation	8
4.1.2.1	GoogleEmailer	8
4.1.2.2	GoogleEmailer	8
4.1.3	Member Function Documentation	8
4.1.3.1	SendMessage	8
4.1.3.2	SendMessage	9
4.1.4	Member Data Documentation	9
4.1.4.1	asyncMessage	9
4.1.5	Property Documentation	9
4.1.5.1	fromAddress	9
4.1.5.2	fromPassword	10
4.1.5.3	toAddress	10
4.2	GoogleCommunication.TestForm Class Reference	10
4.2.1	Detailed Description	10
4.2.2	Member Function Documentation	10
4.2.2.1	Dispose	10

Chapter 1

Namespace Index

1.1 Package List

Here are the packages with brief descriptions (if available):

GoogleCommunication	5
---	---

Chapter 2

Class Index

2.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

GoogleCommunication.GoogleEmailer (This is a small class to help you send emails via the Gmail smtp server, this class is hardcoded for smtp: smtp.gmail.com, using ssl and port:587)	7
GoogleCommunication.TestForm (This is a small Gui, useful for testing your settings and making sure they work. In 3dsmax create an instance of testForm, for ex myForm dotnetclass = "GoogleCommunication.TestForm" myForm.show() --starts the gui)	10

Chapter 3

Namespace Documentation

3.1 Package GoogleCommunication

Classes

- class [GoogleEmailer](#)

This is a small class to help you send emails via the Gmail smtp server, this class is hardcoded for smtp: smtp.gmail.com, using ssl and port:587.

- class **Program**
- class [TestForm](#)

This is a small Gui, useful for testing your settings and making sure they work. In 3dsmax create an instance of testForm, for ex myForm dotnetclass = "GoogleCommunication.TestForm" myForm.show() --starts the gui.

Chapter 4

Class Documentation

4.1 GoogleCommunication.GoogleEmailer Class Reference

This is a small class to help you send emails via the Gmail smtp server, this class is hardcoded for smtp: smtp.gmail.com, using ssl and port:587.

Public Member Functions

- [GoogleEmailer](#) ()
Initializes a new instance of the [GoogleEmailer](#) class.
- [GoogleEmailer](#) (string FromAddress, string FromName, string FromPassword)
Initializes a new instance of the [GoogleEmailer](#) class.
- string [SendMessage](#) (string ToAddress, string ToName, string Subject, string body, bool SendAsync)
Sends the email message.
- string [SendMessage](#) (string ToAddress, string ToName, string Subject, string body, bool SendAsync, string[] Attachments)
Sends the message with attachments.

Public Attributes

- string [asyncMessage](#) = ""
can be useful for debugging

Properties

- MailAddress [fromAddress](#) [get, set]
Gets or sets google account, aka the gmail address. ex. mymail.gmail.com.
- string [fromPassword](#) [get, set]
Gets or sets google account password.
- MailAddress [toAddress](#) [get, set]
Gets or sets the reciever address. This is of type MailAddress, and needs alot of input.

4.1.1 Detailed Description

This is a small class to help you send emails via the Gmail smtp server, this class is hardcoded for smtp: smtp.gmail.com, using ssl and port:587.

4.1.2 Constructor & Destructor Documentation

4.1.2.1 GoogleCommunication.GoogleEmailer.GoogleEmailer ()

Initializes a new instance of the [GoogleEmailer](#) class.

4.1.2.2 GoogleCommunication.GoogleEmailer.GoogleEmailer (string *FromAddress*, string *FromName*, string *FromPassword*)

Initializes a new instance of the [GoogleEmailer](#) class.

Parameters

<i>FromAddress</i>	From address / your gmail account, ex yourmail.gmail.com
<i>FromName</i>	From name / a descriptive name instead of emailaddress ex. "FirstName LastName"
<i>FromPassword</i>	Your Gmail account password

4.1.3 Member Function Documentation

4.1.3.1 string GoogleCommunication.GoogleEmailer.SendMessage (string *ToAddress*, string *ToName*, string *Subject*, string *body*, bool *SendAsync*)

Sends the email message.

Parameters

<i>ToAddress</i>	To address.
<i>ToName</i>	To display name.
<i>Subject</i>	The subject.
<i>body</i>	The body.
<i>SendAsync</i>	if set to <code>true</code> [send async]. The message will be sent asynchronized aka on another thread, letting the application calling this continue the run cycle

Returns

Returns a string with some extra info regarding if the email could be sent

4.1.3.2 `string GoogleCommunication.GoogleEmailer.SendMessage ( string ToAddress, string ToName, string Subject, string body, bool SendAsync, string[] Attachments )`

Sends the message with attachments.

Parameters

<i>ToAddress</i>	To address.
<i>ToName</i>	To name.
<i>Subject</i>	The subject.
<i>body</i>	The body.
<i>SendAsync</i>	if set to <code>true</code> [send async]. Sends the message on another thread..
<i>Attachments</i>	The attachments. And string array contining full paths to files that should be included in the email

Returns

Returns a string with some extra info regarding if the email could be sent. This also returns if there was something wrong with any of the attachments..

4.1.4 Member Data Documentation

4.1.4.1 `string GoogleCommunication.GoogleEmailer.asyncMessage = ""`

can be useful for debugging

4.1.5 Property Documentation

4.1.5.1 `MailAddress GoogleCommunication.GoogleEmailer.fromAddress` [get, set]

Gets or sets google account, aka the gmail address. ex. mymail.gmail.com.

From address.

4.1.5.2 string GoogleCommunication.GoogleEmailer.fromPassword [get, set]

Gets or sets google account password.

From password.

4.1.5.3 MailAddress GoogleCommunication.GoogleEmailer.toAddress [get, set]

Gets or sets the reciever address. This is of type MailAddress, and needs alot of input.

To address.

The documentation for this class was generated from the following file:

- C:/Project/GoogleCommunication - source/GoogleCommunication/WindowsFormsApplication1/GoogleEmailer.cs

4.2 GoogleCommunication.TestForm Class Reference

This is a small Gui, useful for testing your settings and making sure they work. In 3dsmax create an instance of testForm, for ex myForm dotnetclass = "GoogleCommunication.TestForm" myForm.show() --starts the gui.

Protected Member Functions

- override void [Dispose](#) (bool disposing)
Clean up any resources being used.

4.2.1 Detailed Description

This is a small Gui, useful for testing your settings and making sure they work. In 3dsmax create an instance of testForm, for ex myForm dotnetclass = "GoogleCommunication.TestForm" myForm.show() --starts the gui.

4.2.2 Member Function Documentation

4.2.2.1 override void GoogleCommunication.TestForm.Dispose (bool *disposing*) [protected]

Clean up any resources being used.

Parameters

<i>disposing</i>	true if managed resources should be disposed; otherwise, false.
------------------	---

The documentation for this class was generated from the following files:

- C:/Project/GoogleCommunication - source/GoogleCommunication/WindowsFormsApplication1/TestForm.cs
- C:/Project/GoogleCommunication - source/GoogleCommunication/WindowsFormsApplication1/TestForm.Designer.cs

Index

- asyncMessage
 - GoogleCommunication::GoogleEmailer,
[9](#)
- Dispose
 - GoogleCommunication::TestForm, [10](#)
- fromAddress
 - GoogleCommunication::GoogleEmailer,
[9](#)
- fromPassword
 - GoogleCommunication::GoogleEmailer,
[9](#)
- GoogleCommunication, [5](#)
- GoogleCommunication::GoogleEmailer, [7](#)
 - asyncMessage, [9](#)
 - fromAddress, [9](#)
 - fromPassword, [9](#)
 - GoogleEmailer, [8](#)
 - SendMessage, [8](#), [9](#)
 - toAddress, [10](#)
- GoogleCommunication::TestForm, [10](#)
 - Dispose, [10](#)
- GoogleEmailer
 - GoogleCommunication::GoogleEmailer,
[8](#)
- SendMessage
 - GoogleCommunication::GoogleEmailer,
[8](#), [9](#)
- toAddress
 - GoogleCommunication::GoogleEmailer,
[10](#)